

Advanced grinding, it's what a grinder should be...

Erosion Grinding Machine for PCD Tools 6-Axis Full CNC Control With POWERGRIP® System

The flexible, profitable solution

High technology to lead the ever-changing world of tool processing.




SPARQ-PRO, is designed to produce and service PCD cutters . Erosion process is completed in one set-up by means of integral measuring system, in order to achieve high precision and quality, machine main body is produced as single composite monoblock system. Mainly 3 type of tools can be processed by SPARQ-PRO;



Circular Saws, Hoggers and Cutters





Profile knives and moulders

Helical cutters and router bits

A versatile response to meet all demands...



Optional ABM DrawWorks

CAD-CAM software for profiled tools.



Operator friendly ABM-interface for ease of use Positioning display of all 5 axes.



Rapid tool compensation by integral measuring system and wheel dressing unit.


General Features

- 5 axes full CNC control, direct spindle system by additional 6th servo motor.
- Special plating on mechanical components ensure non-corroding and hardening.
- Integral measuring system for complex tool defining.
- Unique interfaces for tool production and service.
- 15" LCD display and operating interface in any stated language.
- Composite monoblock body ensures high rigidity and excellent surface quality.
- · Rapid tool compensating by integral wheel dressing system.
- Wide capacity design to process common type of diamond tools.
- · High volume and pressure of coolant to ensure the best condition for eroding process.
- Smart servo motors without requirement of calibration and referencing.
- Precise ISO 40 system motor controlled dividing head.
- · Central lubrication system.
- Windows based PC control enables update over internet or by flash drive.
- Generator specially designed by ABM.
- · Open software philosophy ensuring unlimited programming ability.
- · Robust based constructed in ergonomic cabin.
- · Production conformed with CE standards.

SPARQ-PRO



At ABM, we develop our machines, our own electronic systems and application software and manufacture all main mechanical components. Finally, we assemble and test the final product to global machine standards. Whichever ABM machine you choose for your grinding, you will know that it is built to meet the all market demands.



- (X) Horizontal Axis
- (Y) Vertical Axis
- (Z) Thickness Axis
- (A) Bevelling Axis
- (B) Power Grip Axis

The true innovation is the product of experience and dynamics...



Aerosol type fire extinguisher system





Central automatic lubrication system, optional coolant micro filtration system and optional air filtration system.



Optional Micro TECH®measuring machine

Technical Specifications

_	Γ_{α}	0	1+01	ni.		eter
	looi	U	пе	1)16	3 F T 1 (erer

- Holder Type
- Tool Weight
- Grinding length
- Grinding Angle
- Bevelling Angle
- Wheel Diameter
- Wheel bore diameter
- Coolant motor capacity
- _____
- Coolant container capacity
- Air supply
- Total Power
- Net/Gross Weight
- Dimensions

Maximum Ø800mm

ISO 40

Maximum 20 kg

Maximum 150mm

360°

360°

Ø125/150mm

Ø60mm

~120 lt/min.

~200 lt

Minimum 6 Bars

~7.5kW

3250/3400 kg

260*210*240 cm





Our path on grinding technologies production started in 1965, continues applying all modern technologies on our services. Not only in local market, our machines are working world-wide with dealers support in 25 countries and with our own sales team in more than 100 different countries.





